Application/Control Number: 10/748,996

Art Unit: 3700

CLMPTO 05/27/04 L.F.

1. (amended) A method for audiological screening of infants and newborns employing a handheld screening device having acoustic transmitters, microphone collection means, scalp electrodes, a digital signal processor, signal transmitters, receivers and a display screen comprising:

a. generating one or more stimuli with the acoustic transmitters of the handheld screening device in each car canal of an infant

or newborn.

b. collecting any transient evoked and/or distortion product otoacoustic emission signals generated by the cochlea in each ear canal in response to the stimulus with the microphone collection means placed in the ear, and/or collecting any click or frequency stimulated brainstem response signals by placing electrodes on the scalp.

TEST AVAILABLE COPY

Application/Control Number: 10/748,996

Art Unit: 3700

c, analyzing the response signals using binomial statistics, different artifact categories by the digital signal processor,

d transmitting all results ("pass", "refer", "technical error') all patient related data and all measurement relevant data (environmental noise, probe lit, electrode impedance, signal to noise ration, etc.) from the handheld screening device transmitter to a patient tracking and screening system installed on a remote computer server via transmission means, such no an analog or digital phone-line, cordless or wireless phone line, power-line, fiber optic line, wireless LAN (blue tooth), satellite telephone line, internet phone, using an external or built-in modern like interface and a predefined protocol, and

g. receiving and displaying on the handheld screening device display screen all patient related data, such as name, first name, mother's name, birth date, address, in/outpatient status, patient identification, hospital identification, patient history directly from a patient tracking

system installed on a main server via a link to the server.

2. (original) A method according to claim 1, wherein the means to transmit the frequency mixed product electric signal from the audiologic screening device to a remote computer system comprises diall-up connections using a built-in or attached analog, digital or mobile-phone modem.

- 3. (amended) A method according to claim 1, wherein the means to transmit the frequency mixed product electric signal from the audiologic screening device to a remote computer system comprises LAN connections to transfer and receive data in email-, ftp-, and internet or other-protocols.
- 4. (amended) A method according to Claim 1, wherein the remote computer server receives and transmits screening and patient data via the patient tracking and screening system, which also controls the handheld screening device procedures with respect to:
 - a. setting the real time clock of the screener user,
- b. providing program parameters, such as -service-intervals; witerions, measurement methods;
 - e. uploading software upgrades to the a device.
- d. sending messages to the screener user, including serviceissues and procedures.
- 5. (original) A method according to Claim 4, wherein the patient information includes a list of patients that are to be tested next, along with information on the patients required by the screening program, and other related information including known risk factors or general comments.
- (original) A method according to Claim 1 wherein the nudiologic screening device is programmable from the remote computer server.
- 7. (original) A method according to Claim 1, wherein the remote computer server receives and transmits according and patient data

Application/Control Number: 10/748,996

Art Unit: 3700

D)

via the patient tracking and screening system, which also controls the handheld screening device procedures with respect to:

a. setting the real time clock of the screener user,

 providing program parameters, such as service-intervals, criterions, measurement methods,

c. uploading software upgrades to the device.

d. sending messages to the screener user, including service-issues and procedures.

 (original) A method according to Claim 7 wherein the service-issues are dependent on measurement results.

- 9, (amended) A method according to Claim 1 including combining an audiologic screening database with other newborn screening data, like metabolic disease screening data; and using and accessing to a commonly used database on a computer or server which generates and then stores all patient and result data for different screening methods.
- 10. (amended) A device for audiological screening of infants and newborns comprising:

a. means for generating one or more stimuli with acoustic transmitters in each ear caust of an infant or newborn,

b. means for collecting any transient evoked and distortion product otoacoustic emissions generated by the cochlea in each car canal in response to the stimulus with microphone means for generating a frequency mixed product electric signal, and brain stem responses via scalp attached electrodes,

c. means for analyzing the response signals using binomial statistics, different artifact categories by a digital signal processor

associated with the signal collecting means,

- d. means for transmitting the results ("pass, reter, technical error"), all patient related data and all measurement relevant data such as environmental noise, probe-fit, electrode impedance, signal to noise ratio, etc. directly from the screening device to a patent tracking system installed on a remote computer server, and
- e. means for receiving and displaying on the handheld screening device display all patient related data such as name, first name, mother's name, birth date, address, in outpatient status, patient identification, hospital identification patient history, etc. directly from a patient tracking system installed on a main server.
- 11. (original) A device for audiological screening of infants and newborns according to Claim 10, wherein the means for transmitting to the remote server is a modern in communication with the computer server.
- 12. (amended) A device for audiological screening of infants and newborns according to Claims 10, including a combined audiologic screening database with other newborn screening data, like metabolic disease screening data inputted into the computer server, which generates and stores all patient and result data for different screening methods.

Art Unit: 3700

- 13. (original) A device for audiological screening of infants and newborns according to Claim 10, wherein the connection means for transmitting data includes:
 - a. sending patient lists to the screener,
- b. updating or changing configuration information on the interconnected devices,
 - e. transferring and installing new software on the screener,
 - d. setting the real time clock of the screener, and/or
- e. transferring messages to the user, patient related, device related and service instructions
- 14. (original) A device for audiological screening of infants and newborns according to Claim 13, wherein the service-issues messages may be dependent on measurement results.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original

documents submitted by the applicant.	2 yenerge og stiller i det
Defects in the images include but are not limited	d to the items checked:
☐ BLACK BORDERS	
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES	
☐ FADED TEXT OR DRAWING	. টিগুলেম্ড্রেসেক
BLURRED OR ILLEGIBLE TEXT OR DRAWING	Fig. 1931, and solven
☐ SKEWED/SLANTED IMAGES	1 To the in appear for 12 a
☐ COLOR OR BLACK AND WHITE PHOTOGRAP	HS 43 60101 0011/
GRAY SCALE DOCUMENTS	THE AMELIAN
☐ LINES OR MARKS ON ORIGINAL DOCUMENT	Dunisorman
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED A	RE POOR QUALITY TO REPORT (L.)
OTHER:	Tarana.

IMAGES ARE BEST AVAILABLE COPY. HAGES ARE AS rescanning these documents will not correct the image ing problems checked, please do not report these problems to hecked the IFW Image Problem Mailbox.